

County Surveyor's Record, Douglas County, Oregon

17882 Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

The north fork of a sawed twin fir stump, 28 ins. diam., bears N. 59° E., 34½ lks. dist., with chopped open blaze, no marks visible. (Record, 32 lks.)

and the remains of a bearing tree mkd. by Thiel

A root crown, with maple shoots, bears N. 13° W., 84 lks. dist., alongside of which is a down maple, 8 ins. diam., nomarks visible.

and bearing trees mkd. by Wenderoth

A maple, 14 ins. diam., bears N. 44° E., 55 lks. dist., with healed blaze.

A maple, 10 ins. diam., bears S. 74 3/4° E., 56 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W
S 21 S 22

S 27
1983

from which a new bearing tree

A fir, 6 ins. diam., bears N. 31° W., 25½ lks dist., mkd. T32S R5W S21 BT.

Corner is located in ravine, drains N. 20° W.

N. 89° 10' W., on the S. bdy. of sec. 21.

Ascend over NE. slope, through heavy timber and dense undergrowth.

1.10 True point for the closing cor. of secs. 27 and 28, hereinafter described.

Ascend over NE. slope.

5.45 Spur ridge, slopes N.; desc. over W. slope.

40.27 The ¼ sec. cor. of secs. 21 and 28, reestablished by proportionate measurement and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1956, and is accepted as the best available evidence of the position of the original corner, monumented with an iron wagon axle, 2 ins. diam., firmly set, projecting 29 ins. above ground, from which bearing trees mkd. by Wenderoth:

The south fork of a twin black oak, 19 ins. diam., bears N. 61½° E., 119 lks. dist., with healed blaze.

A white oak, 12 ins. diam., bears S. 38¼° W., 70 lks. dist., with healed blaze.

At the corner point