

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17883
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
¼ S 21
 S 28
 1983

Reset wagon axle alongside iron post.

Corner is located at intersection of fences, extending E., W., And N.

N. 89° 09' W., beginning new measurement.

Descend along N. slope, through scattering timber and light undergrowth.

19.85 Stumbo Road, gravelled, 25 lks. wide, bears N. and S.

20.00 Power transmission line, bears N. and S.

20.415 A corner, established and recorded by Max H. Hull, Registered Land Surveyor, No. 901, in 1975, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of a bearing tree and bearing object mkd. by Hull:

A fence corner, bears N. 88° E., 28 lks. dist.

A sawed ponderosa pine stump, 36 ins. diam., bears S. 29° W., 30½ lks. dist., no marks visible.

37.65 Creek, dry, 8 lks. wide, course S. 40° W.; asc. over gentle slope.

40.83 The corner of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 32 S R 5 W
 S 20 | S 21
 S 29 | S 28
 1962

from which bearing trees mkd. by the County Surveyor's Office

A ponderosa pine, 45 ins. diam., bears S. 58° E., 111 lks. dist., with healed blaze. (Record, S. 55½° E., 109 lks.)

A fir, 18 ins. diam., bears N. 78° W., 69 lks. dist., with healed blaze. (Record, N. 75 3/4° W.)

and a bearing tree and bearing object mkd. by Gawron and McDonald.

An ash, 8 ins. diam., bears S. 49½° E., 143 lks. dist., with healed blaze. (Record S. 45° E.)

An iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, bears N. 21 3/4° W., 46 lks. dist. (Record, N. 19° W.)