

County Surveyor's Record, Douglas County, Oregon

17884 Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

and a new bearing tree

A cedar, 6 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ E., 115 lks.
dist., mkd. T32S R5W S21 BT.

No other suitable trees available within limits

Corner is located in a fence, extends N. and S.

From this point, United States Coast and Geodetic Survey
triangulation station "GOAT" bears N. $29^{\circ} 30'$ E.,
254.89 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins.
diam., firmly set, projecting 4 ins. above ground, with
brass cap mkd. GOAT USC&GS 1963.

Land, mountainous and rolling valley floor.

Soil, rocky clay.

Timber, pine, fir, cedar, maple, oak, ash, dogwood, and
madrone; undergrowth, poison oak, ceanothus, Oregon
grape, manzanita, grass, and weeds.

From the cor. of secs. 27, 28, 33, and 34.

N. $0^{\circ} 50'$ E., bet. secs. 27 and 28.

Descend along broken E. slope, through heavy timber and
dense undergrowth.

2.20 Ravine, drains E.; asc. over SE. slope.

4.65 Spur, slopes E.; desc. over NE. slope.

7.55 Ravine, drains S. 70° E.; asc. over SE. slope.

10.35 Spur, slopes E.; desc. over NE. slope.

13.10 Ravine, drains E.; asc. over SE. slope.

14.85 Spur, slopes E.; desc. over NE. slope.

16.00 Ravine, drains N. 85° E.; asc. over SE. slope.

23.70 Dirt road, 25 lks. wide, bears N. 70° E., and S. 70° W.

27.70 Spur, slopes S. 70° E.; desc. over NE. slope.

39.15 Ravine, drains S. 50° E.; asc. over SE. slope.

39.56 The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, perpetuated and recorded
by George J. Wenderoth, Registered Land Surveyor, No. 5,
in 1956, from original evidence no longer in existence,
monumented with an iron pipe, $\frac{3}{4}$ ins. diam., firmly set
projecting 6 ins. above ground, from which bearing trees
mkd. by Wenderoth:

A fir, 40 ins. diam., bears S. $87\frac{1}{4}^{\circ}$ E., $40\frac{1}{2}$ lks.
dist., with healed blaze.

A fir, 18 ins. diam., bears N. 69° W., $15\frac{1}{2}$ lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, directly over iron pipe, with brass cap
mkd.