

County Surveyor's Record, Douglas County, Oregon

17885

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 32 S R 5 W
 $\frac{1}{4}$
 S 28 | S 27
 1983

N. 0° 35' W., beginning new measurement.

Ascend over SE. slope.

3.20 Spur, slopes S. 65° E.; desc. along E. slope.

21.95 Spur, slopes N. 25° E.; desc. over NW slope.

32.50 Spur, slopes N. 55° W.; desc. over broken NE. slope.

39.705 The original closing cor. of secs. 27, and 28, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1956, monumented with an iron pipe, 3/4 ins. diam., firmly set, projecting 6 ins. above ground, from which the remaining original bearing tree:

A fir, 56 ins. diam., bears S. 32 3/4° E., 53 lks. dist., with illegible scribe marks visible on chopped open blaze. (Record, S. 30° E.)
 And the remains of a bearing tree mkd. by Wenderoth

A root hole, bears S. 18 3/4° E., 79 lks. dist., alongside of which is a down maple, 13 ins. diam., with chopped, decayed blaze, no marks visible.

39.72 Intersect the S. bdy. of sec. 21.

True point for the closing cor. of secs. 27 and 28.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 21
 S 28 | S 27
 T 32 S | R 5 W
 C C
 1983

from which

A maple, 9 ins. diam., bears S. 67 1/2° E., 106 lks. dist., mkd. T32S R5W S27 CC BT.

A fir, 9 ins. diam., bears S. 30 1/2° W., 23 lks. dist., mkd. T32S R5W S28 CC BT.

From this point, the cor. of secs. 21 and 22 only, bears S 89° 10' E., 1.10 chs. dist., hereinbefore described.

Land, mountainous.
 Soil, rocky clay.
 Timber, pine, fir, cedar, maple, oak, dogwood, and madrone;
 undergrowth, poison oak, ceanothus, Oregon grape, manzanita,
 grass, and weeds.