

County Surveyor's Record, Douglas County, Oregon

17887

Subdivision of Section 23,
T. 32 S., R. 5 W., Willanette Meridian, Oregon

CHAINS

From the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

N. $0^{\circ} 29'$; W., on the N. and S. center line of sec. 23.

Ascend over SE. slope, changing to SW. slope, through heavy timber and dense undergrowth.

8.00 Ridge, bears N. 40° W. and S. 40° E.; desc. over NE. slope.

14.60 Ravine, drains N. 45° E.; asc. along E. slope, changing to NE. slope.

20.13 From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, bears East, 0.19 chs. dist., monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Wenderoth:

A fir, 19 ins. diam., bears N. 65° E., 82 lks. dist., with healed blaze.

A cedar, 29 ins. diam., bears N. 83° W., 58 lks. dist., with healed blaze.

22.30 Top of ascent, slopes E.; desc. over broken NE. slope.

30.80 Terminus of gravelled road, 30 lks. wide, extends E., curving to S. 20° E.

39.65 Creek, 3 lks. wide, course N. 60° W.; asc. over SW. slope.

40.27 Point for the center $\frac{1}{4}$ sec. cor. of sec. 23, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
C $\frac{1}{4}$ S 23
1983

from which

A fir, 18 ins. diam., bears S. $77\frac{3}{4}^{\circ}$ E. $34\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S23 BT.

A fir, 13 ins. diam., bears N. $20\frac{3}{4}^{\circ}$ W., $36\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S23 BT.

From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, bears N. $75^{\circ} 48'$ E., 0.155 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Wenderoth:

A fir, 26 ins. diam., bears N. 78° E., $78\frac{1}{2}$ lks. dist., with healed blaze.

A cedar, 32 ins. diam., bears N. 2° W., 102 lks. dist., with healed blaze.

Ascend over SW. slope, changing to gentle W. slope.