

# County Surveyor's Record, Douglas County, Oregon

17889

Subdivision of Section 23,  
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
12.75	Ravine, drains N. 30° W.; asc. over broken NE. slope, changing to N. slope.
24.40	Spur, slopes N. 65° W.; desc. over NW. slope, changing to SW. slope.
29.90	Gravelled road, 30 lks. wide, bears N. 20° E. and S. 20° W.
41.72	The center $\frac{1}{4}$ sec. cor. of sec 23.
43.30	Descend over SW. slope. Creek, 3 lks. wide, course N. 60° W.; asc. over NE. slope, changing to broken N. slope.
62.08	From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, bears North, 0.065 chs. dist., monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Wenderoth:  <div style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 70° E., 48 lks. dist., with healed blaze.</div> Corner is located in wire fence, extending N. and S.
62.35	Spur, slopes N.; desc. over NW. slope.
82.60	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
From the N. $\frac{1}{16}$ sec. cor. of secs. 23 and 24.	
N. 89° 30' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 23.	
Descend over SW. slope, through heavy timber and dense undergrowth.	
13.30	Gravelled road, 30 lks. wide, bears N. 80° W. and S. 25° W., in curve.
29.00	Ravine, drains N. 45° E.; asc. along broken N. slope.
35.65	Spur, slopes N. 20° W.; desc. over NW. slope.
37.50	Dirt road, 15 lks. wide, bears N. 35° W. and S. 65° E., in curve.
40.85	The center N $\frac{1}{16}$ sec. cor. of sec. 23.
Subdivision of Section 27, T. 32 S., R. 5 W., Willamette Meridian, Oregon	
From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.	
N. 5° 41' W., on the N. and S. center line of sec. 27.	
Descend over N. slope, through heavy timber and dense undergrowth.	
0.90	Wet ravine, drains N. 20° E.; asc. over broken SE. slope.