

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

17895

**CHAINS**

Beginning at the N 1/16 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins., diaml, firmly set, projecting 4 ins. above ground, with brass cap mkd.

N 1/16  
S 15 | S 14  
1962

from which a bearing tree mkd. by White, Beck, and Reynolds.

A cedar, 28 ins. diam., bears N. 75½° W., 43 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A fir, 4 ins. diam., bears N. 49° E., 5 lks. dist., mkd. X BT.

N. 2° 09' W., bet. secs. 14 and 15, marking and blazing the true line.

Ascend over SW. slope, through scattering timber and dense under growth.

- 8.55 Spur, slopes SW.; desc. over NW. slope.
- 11.40 Ravine, drains S. 60° W.; asc. over SW. slope
- 14.50 Spur, slopes W ; desc. over NW. slope.
- 18.20 Ravine, drains NW.; asc. over SW. slope.
- 20.48 The cor. of secs. 10,11,14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 26 S R 3 W  
S 10 | S 11  
S 15 | S 14  
1962

from which the remains of the original bearing trees

A fir, 28 ins. diam., bears S 72° W., 11 lks. dist., no marks visible.

A fir stump, 42 ins. diam., bears N. 46° W., 27½ lks. dist., with scribe marks T26S R3W S10 BT visible on bark blaze.

and the remains of bearing trees mkd. by G. G. Stewart, County Surveyor, in 1922

A rotted fir snag, 28 ins. diam., bears N. 32° E., 33 lks. dist., no marks visible.

A fir, 38 ins. diam., bears S. 58° E., 66 lks. dist., with scribe marks CS S14 BT visible on bark blaze.

A yew, 16 ins. diam., bears, S. 41° W., 29 lks. dist., with healed double blaze.