

County Surveyor's Record, Douglas County, Oregon

17896 Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by White, Beck, and Reynolds

A cedar, 27 ins. diam., bears N. 47° E., 110 lks. dist., with
healed blaze.

No suitable trees available within limits in sec. 10.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, hemlock, oak, yew, and dogwood; under-
growth, vinemaple, poison oak, salal, hazel, and fern.

Subdivision of Section 15, T. 26 S., R. 3 W.,
Willamette Meridian, Oregon

From the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented with an iron
post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground,
with brass cap mkd.

T 26 S R 3 W
 $\frac{1}{4}$ S 15
S 22
1962

from which the remains of bearing trees mkd. by White, Beck, and
Reynolds

A cedar stump, 21 ins. diam., bears S. 51° E., 80 lks. dist.,
with fragmentary scribe marks visible on partially healed
blaze.

A fir snag, 54 ins. diam., bears N. 5° W., 125 lks. dist.,
with fragmentary scribe marks visible on partially healed
blaze.

and new bearing trees

A fir, 8 ins. diam., bears S. 4° E., 5 lks.
dist., mkd. $\frac{1}{4}$ S22 BT.

A fir, 5 ins. diam., bears N. 18° W., 17 lks.
dist., mkd. X BT

N. 1° 31' W., on the N. and S. center line of sec. 15,
marking and blazing the true line.

Descend over N. slope, through heavy timber and dense
undergrowth.

11.90 Dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.

20.28 Point for the center S 1/16 sec. cor. of sec 15.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

C
S 1/16 | S 15
C
1984