

# County Surveyor's Record, Douglas County, Oregon

17897

Subdivision of Section 15, T. 26 S., R. 3W.,  
Willamette Meridian, Oregon

**CHAINS**

from which

A cedar, 20 ins. diam., bears N. 65° E., 6 lks.  
dist., mkd. CS 1/16 S15 BT.

A white fir, 20 ins. diam., bears N. 63° W.,  
35 lks. dist., mkd. CS 1/16 S15 BT.

Descend over NW. slope.

21.95 Gravelled road, 20 lks. wide, bears N. 70° E. and  
S. 70° W.

40.56 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 15, at  
intersection with the E. and W. center line.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 26 S R 3 W  
C  $\frac{1}{4}$   
S 15  
1984

from which

A fir, 3 ins. diam., bears N. 50 $\frac{1}{2}$ ° E., 10  
lks. dist., mkd. X BT

A yew, 15 ins. diam., bears S. 28 $\frac{3}{4}$ ° W., 46  
lks. dist., mkd. C  $\frac{1}{4}$  S 15 BT.

Descend over NW. slope.

60.92 Point for the center N 1/16 sec. cor. of sec. 15.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., with  
plastic magnetic breakaway base. 26 ins. in the ground,  
with brass cap mkd.

C  
N 1/16 | S 15  
C  
1984

from which

A cedar, 27 ins. diam., bears N. 41 $\frac{1}{2}$ ° E., 61  
lks. dist., mkd. CN 1/16 S 15 BT

A white fir, 9 ins. diam., bears S. 30° W., 9 lks.  
dist., mkd. CN 1/16 S 15 BT.

Descend over NW. slope.

63.65 Creek, 5 lks. wide, course N. 45° E.; asc over SE.  
slope.

81.28 The  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, monumented with an  
iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 2 ins.  
above ground, with brass cap mkd.

T 26 S R 3 W  
 $\frac{1}{4}$  S 10  
S 15  
1962