

County Surveyor's Record, Douglas County, Oregon

17898

Subdivision of Section 15, T. 26 S., R. 3 W.,
Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. by A. R. Evans, Registered Engineer No. 2741, in 1951

A fir, 17 ins. diam., bears S. 1° W., 26 lks. dist., with healed double blaze.

A fir, 25 ins. diam., bears N. 67° W., 24 lks. dist., with healed double blaze.

From this point, Douglas County Surveyor's Office Horizontal Control Station "SWIFTWATER 1978", bears N. 55° 15' E., 171.63 chs, dist., monumented with a brass tablet, 3 ins. diam., set in drill hole, in concrete guardrail on Swiftwater Bridge, with top mkd. DOUGLAS COUNTY SURVEYORS OFFICE SWIFTWATER 1978.

From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap missing, from which the remains of bearing trees mkd. by White, Beck, and Reynolds:

A cedar stump, 28 ins. diam., bears N. 20 $\frac{1}{2}$ ° E., 60 lks. dist., with scribe marks $\frac{1}{4}$ S14 BT on partially healed blaze.

A cedar, 23 ins. diam., bears N. 75° W., 29 lks. dist., with; healed blaze.

At the corner point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., with plastic magnetic breakaway base, 24 ins. in the ground, with brass cap mkd.

T 26 S R 3 W

$\frac{1}{4}$
S 15 | S 14
1984

from which a new bearing tree

A pine, 8 ins. diam., bears S. 26° E., 41 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Deposit 1962 iron post alongside new iron post.

N. 89° 47' W., on the E. and W. center line of sec. 15.

Descend over W. slope.

4.15 Britt Creek, 10 lks. wide, course N. 5° E.; asc. over broken NE. slope.

17.05 Gravelled road, 20 lks. wide, bears N. 5° W. and S. 15° E.

20.06 Point for the center E $\frac{1}{16}$ sec. cor. of sec. 15.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., with plastic magnetic breakaway base, 22 ins. in the ground, with brass cap mkd.

$\frac{E \ 1/16}{C}$
S 15
1984