

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 26 S., R. 3 W., 17899  
Willamette Meridian, Oregon

**CHAINS**

from which

A cedar, 26 ins. diam., bears N. 70½° E.,  
18 lks. dist., mkd. CE 1/16 S15 BT.

A fir, 25 ins. diam., bears S. 38½° W.,  
24 lks. dist., mkd. CE 1/16 S15 BT.

Ascend over broken NE slope.

26.10 Spur, slopes N. 30° E.; desc. over NW. slope.

28.30 Gravelled road, 20 lks. wide, bears N. 10° E. and  
S. 25° W.

40.12 The center ¼ sec. cor. of sec. 15.

Descend over NW. slope.

44.00 Creek, 5 lks. wide, course N. 10° E.; asc. over E. slope.

57.15 Gravelled road, 15 lks. wide, bears N. 30° E. and  
S. 30° W.

60.23 Point for the center W 1/16 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins.  
in the ground, with brass cap mkd.

C  $\frac{W\ 1/16}{S\ 15}$  C  
1984

from which

A fir, 5 ins. diam., bears S. 81½° E., 22 lks.  
dist., mkd. CW 1/16 S15 BT.

A fir, 9 ins. diam., bears N. 37½° W., 26 lks.  
dist., mkd. CW 1/16 BT.

Ascend over E. slope.

80.34 The ¼ sec. cor. of secs. 15 and 16, monumented with an  
iron post, 2½ ins. diam., firmly set, projecting 4 ins.  
above ground with brass cap mkd.

T 26 S R 3 W  
¼  
S 16 | S 15  
1962

from which bearing trees mkd. by White, Beck, and  
Reynolds

A cedar, 15 ins. diam., bears S. 84° E. 69  
lks. dist., with healed blaze.

A cedar, 14 ins. diam., bears N. 71° W., 48  
lks. dist., with healed blaze.

From the center E 1/16 sec. cor. of sec. 15.  
N. 1° 56' W., on the N. and S. center line of the NE¼ of  
sec. 15.  
Descend over N. slope, through heavy timber and dense  
undergrowth.