

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15. T. 26 S., R. 3 W.
Willamette Meridan, Oregon

17901

CHAINS

From the N 1/16 sec. cor. of secs. 14 and 15.

N. 89° 54' W., on the E. and W. center line of the NE¼ of sec. 15.

Descend over NW. slope, through heavy timber and dense undergrowth.

8.80 Britt Creek, 10 lks. wide, course N.; asc. over NE. slope.

14.30 Spur, slopes N. 20° E.; desc. over NW. slope.

19.87 The NE 1/16 sec. cor. of sec. 15.

Descend over NW. slope.

22.75 Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.

26.75 Creek, 3 lks. wide, course N. 15° W.; asc. over E. slope.

31.75 Ridge, bears N. 20° E. and S. 20° W.; desc. over W. slope.

39.78 The center N 1/16 sec. cor. of sec. 15.

From the E 1/16 sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

$$\begin{array}{c} \text{S } 15 \\ \text{E } 1/16 \text{ S } 22 \\ 1962 \end{array}$$

from which the remains of a bearing tree mks. by White, Beck, and Reynolds

A hemlock stump, 10 ins. diam., bears N. 16° W.,
46 lks. dist., with healed blaze.

and new bearing trees

A fir, 7 ins. diam., bears S 46½° E., 37 lks.
dist., mkd. E 1/16 S22 BT.

A fir, 4 ins. diam., bears N. 33 3/4° W., 5 lks.
dist., mkd. X BT.

N. 1° 57' W., on the N. and S. center line of the SE¼ of sec. 15.

Descend over NE. slope, through scattering timber and dense undergrowth.

13.40 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.

20.37 Point for the SE 1/16 sec. cor. of sec 15, at intersection with the E. and W. center line of the SE¼ of sec. 15.