

County Surveyor's Record, Douglas County, Oregon

17902

Subdivision of Section 15, T. 26 S., R. 3 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 15 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 54° E., 89½ lks. dist., mkd. SE 1/16 S15 BT.</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 51½° W., 203 lks. dist., mkd. SE 1/16 S15 BT.</p> <p>Corner is located on S. edge of dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.</p> <p>Descend over NE. slope.</p>
40.76	<p>The center E 1/16 sec. cor. of sec. 15.</p>
	<p>From the S 1/16 sec. cor. of secs. 14 and 15 monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 15 S 14 1962</p> <p>from which the remains of bearing trees mkd. by White, Beck, and Reynolds</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 18° E., 39 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar stump, 20 ins. diam., bears S. 63° W., 52 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears N. 63° W. 31 lks. dist., mkd. S 1/16 S15 BT.</p> <p>N. 89° 31' W., on the E. and W. center line of the SE¼ of sec. 15.</p> <p>Ascend over NE. slope, through scattering timber and dense overgrowth.</p>
13.45	<p>Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.</p>
17.45	<p>Creek, 2 lks. wide, course N. 5° E.; asc. over NE. slope.</p>
20.11	<p>Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.</p>
20.24	<p>The SE 1/16 sec. cor. of sec 15.</p> <p>Ascend over NE. slope.</p>
33.00	<p>Spur, slopes N. 15° E.; desc. over W. slope.</p>