

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 26 S., R. 3 W.,  
Willamette Meridian, Oregon

17903

**CHAINS**

40.46

The center S 1/16 sec. cor. of sec. 15.

From the center W 1/16 sec. cor. of sec. 15.

N. 1° 06' W., on the N. and S. center line of the NW $\frac{1}{4}$  of sec. 15.

Descend over NW. slope, through heavy timber and moderate undergrowth.

8.35

Creek, 3 lks. wide, course N. 50° E.; asc. over SE. slope.

12.30

Spur, slopes N. 60° E.; desc. over NE. slope.

20.23

Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NW $\frac{1}{4}$  of sec. 15.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., with plastic magnetic breakaway base, 24 ins. in the ground, with brass cap mkd.

NW 1/16  
S 15  
1984

from which

A fir, 14 ins. diam., bears N. 44° E., 33 lks. dist., mkd. NW 1/16 S15 BT.

A cedar, 17 ins. diam., bears S. 39 $\frac{1}{2}$ ° W., 59 lks. dist., mkd. NW 1/16 S15 BT.

Descend over NE. slope.

40.15

Creek, 5 lks. wide, course N. 45° E.; asc. over SE. slope.

40.44

The W 1/16 se. cor. of secs. 10 and 15, monumented with an iron post, 2 $\frac{1}{2}$  ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

W 1/16  $\frac{S 10}{S 15}$   
1962

from which bearing trees mkd. by White, Beck and Reynolds

A cedar, 20 ins. diam., bears N. 62° E., 3 lks. dist., with healed blaze. (Record, S. 34° E.)

A fir, 36 ins. diam., bears S. 39° E., 89 lks. dist., with healed blaze. (Record, S. 34° E.)

From the center N 1/16 sec. cor. of sec. 15

S. 89° 56' W., on the E. and W. center line of the NW $\frac{1}{4}$  of sec. 15.

Descend over NE. slope, through heavy timber and dense undergrowth.