

County Surveyor's Record, Douglas County, Oregon

17998

Corrective Dependent Resurvey
 Portion of the Subdivisional Lines
 T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

N.0° 39' W., bet. secs. 26 and 27, marking and blazing the true line.

Ascend over SE. slope, through heavy timber and dense undergrowth.

3.90 Spur, slopes E.; desc. over N. Slope.

5.45 Dry creek bed, 10 lks. wide, course S. 50° E.; asc. over broken SE. slope.

30.40 Dirt road, 15 lks. wide, bears S. 85° E. and S. 75° W., in curve.

33.62 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidences of the original corner.

From this point the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, erroneously reestablished by Wofford, Rogers, and Chatters, in 1973-79, bears N. 7° 44' E., 0.94 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, destroy the marks on the bearing trees, and at the true corner point

Reset the iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in ground, with brass cap mkd.

T 22 S R 9 W
 $\frac{1}{4}$
 S 27 | S 26
 1983

from which

A fir, 11 ins. diam., bears N. 81° E.,
 41 lks. dist., mkd. $\frac{1}{4}$ S26 BT.

A fir, 27 ins. diam., bears S. 30 3/4° W.
 40 lks. dist., mkd. $\frac{1}{4}$ S 27 BT.

From this same point, a point established by person (s) unknown, bears S. 59 $\frac{1}{2}$ ° E., 18 $\frac{1}{2}$ lks. dist., monumented with an iron pipe, 1 3/4 ins. diam., firmly set, projecting 14 ins. above the ground.

The corner is located on steep SE. slope.

Continue ascent over SE. slope.

35.40 Spur ridge, bears N. 45° E. and S. 70° W.; also dirt road, 15 lks. wide, bears the same; desc. over NW. slope.

40.00 Ravine, drains NW.; asc. over SW. slope.

48.30 Spur, slopes W.; desc. over NW. slope.

73.18 The cor. of secs. 22, 23, 26, and 27, monumented with the original sandstone, 10x8x4 ins., loosely set, projecting 3 ins. above ground, mkd. with 2 notches on S. and E. edges, from which the remains of the original bearing trees