

County Surveyor's Record, Douglas County, Oregon


17912

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Remove the iron post, destroy the marks on the bearing trees, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A fir, 25 ins. diam., bears N. 49° E.,
65 lks. dist., mkd. N 1/16 S 23 BT.

A fir, 17 ins. diam., bears N. 36° W.,
42 ½ lks. dist., mkd. N 1/16 S22 BT.


Continue descent over NW. slope

71.60 Creek, 1 lk. wide, course N. 35° W.; asc. over SW. slope.

74.30 Spur, slopes W.; desc. over NW. slope.

79.81 Creek, 20 lks. wide, course N. 75° W.; asc. over SW. slope.

80.90 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which the remaining original bearing trees

A fir, 45 ins. diam., bears N. 65° E.,
32 lks. dist., with healed blaze.

A fir, 50 ins. diam., bears S. 22° W.,
100 lks. dist., with healed blaze.

and a bearing tree mkd. by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1967.

A fir 8 ins. diam., bears N. 31 ½° W.,
36 lks. dist., with healed blaze.

and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1968

A fir, 10 ins. diam., bears S. 75° E.,
91 lks. dist., with healed blaze.

and a bearing tree mkd. by Wofford, Rogers, and Chatters,

A fir, 13 ins. diam., bears N. 46 ½° W.,
46 lks. dist., with healed blaze.