

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,  
 Portion of the Subdivisional Lines  
 T. 22 S., R. 9 W., Willamette Meridian, Oregon

17919

**CHAINS**

dist., monumented with an iron post, 2 ½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2 ½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	R 9 W
S 28	S 27
C	C
S 34	

1984

from which bearing trees mkd. by Wofford, Rogers, and Chatters

A hemlock, 21 ins. diam., bears N. 43 ¼° E., 47 lks. dist., with scribe marks S27 CC Bt visible on partially healed blaze.

A fir, 45 ins. diam., bears N. 66 ½° W., 59 lks. dist., with healed blaze.

From this point the cor. of secs. 33 and 34, bears N. 84° 26' W., 7.68 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, alder, maple, and myrtle; undergrowth, fern, blackberry, salmonberry, arrowwood, Oregon grape, salal, and poison oak.

Point for the ¼ sec. cor. of sec. 27 only, is at midpoint in departure, on the S. bdy. of sec. 27.

From this point the ¼ sec. cor. of sec. 27 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears S. 70° 18' W., 0.06 chs. dist., monumented with an iron post, 2 ½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post and at the true corner point

Reset the iron post, 28 ins. long, 2 ½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	R 9 W
¼	S 27
1984	

from which bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 13 ins. diam., bears N. 70° E., 30 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 52 ¾° W., 17 lks. dist., with healed blaze.