

County Surveyor's Record, Douglas County, Oregon

17922

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS							
20.80	Spur, slopes SE.; asc. over SW. slope.						
32.90	Spur, slopes SW.; desc. over N. slope.						
36.70	Ravine, drains N. 35° W.; asc. over SW. slope.						
38.27	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.						
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T 22S R 9 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> </table>	T 22S R 9 W		S 16	S 15	S 21	S 22
T 22S R 9 W							
S 16	S 15						
S 21	S 22						
	1973						
	from which the remains of an original bearing tree						
	A decayed fir stump, 64 ins. diam., bears N. 10° W., 25 lks. dist., no marks visible						
	and bearing; trees mkd. by Harold T. Lewis, Registered Engineer No. 722, in 1939						
	A fir, 18 ins. diam., bears N. 45° E., 15 lks. dist., with healed blaze.						
	A fir, 17 ins. diam., bears S. 84° E., 17 lks. dist., with healed blaze.						
	A fir, 35 ins. diam., bears N. 40° W., 82 lks. dist., with healed blaze.						
	and a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962						
	A fir, 33 ins. diam., bears S. 66° W., 51 lks. dist., with healed blaze.						
	and a bearing tree mkd. by Wofford, Rogers, and Chatters						
	A fir, 14 ins. diam., bears N. 85° E., 18 lks. dist., with healed blaze.						
	Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, oak, maple, and alder; undergrowth, fern, vine maple, salal, Oregon grape, poison oak, blackberry, thimbleberry, and rhododendron.						
	From the cor. of secs. 33 and 34 only.						
	N. 89° 32' W., on the N. bdy. of sec. 33.						
	Ascend over broken NE. slope, through heavy timber and dense undergrowth.						
6.90	Top of rock bluff, 25 ft. high, edge bears S. 30° E. and N. 30° W.						
9.85	Spur, slopes S.; desc. over broken W. slope.						
27.25	Ravine, drains S. 15° W., asc. over broken SE. slope.						
33.65	Point for the ¼ sec. cor. of sec. 28 only, at proportionate dist., on the S. bdy. of sec. 28.						