

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,  
Portion of the Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

17923

**CHAINS**

From this point, the  $\frac{1}{4}$  sec. cor. of sec. 28 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears S.  $76^{\circ} 57'$  W., 0.18 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, destroy the marks on NE. bearing tree, and at the true corner point

Reset the iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W  
           $\frac{1}{4}$  S 28

1984

from which a bearing tree mkd. by Wofford, Rogers, and Chatters

A fir, 15 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  W.,  
43  $\frac{1}{2}$  lks. dist., with healed blaze.

and a new bearing tree

A fir, 15 ins. diam., bears N.  $6\frac{3}{4}^{\circ}$  E.,  
35 lks. dist., mkd.  $\frac{1}{4}$  S28 BT.

ascend over SE slope.

39.15

Point for the  $\frac{1}{4}$  sec. cor. of sec. 33 only, at proportionate dist.; there is no remaining evidence of the original corner.

From this point the  $\frac{1}{4}$  sec. cor. of sec. 33 only, erroneously reestablished by Wofford, Rogers, and Chatters, in 1973-79, bears N.  $55^{\circ} 42'$  E., 0.15 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

           $\frac{1}{4}$  S33  
T 22 S R 9 W  
1984

from which the bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 11 ins. diam., bears N.  $89\frac{3}{4}^{\circ}$  E.,  
58  $\frac{1}{2}$  lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S.  $67^{\circ}$  W.,  
19  $\frac{1}{2}$  lks. dist., with healed blaze.