

County Surveyor's Record, Douglas County, Oregon

17924

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Ascend over SE. slope

39.80 Top of ascent, slopes S.; desc. over broken SW. slope

45.40 Ravine, drains S.; asc. over SE. slope.

50.95 Spur, slopes S.; desc. over SW. slope.

53.185 Point for the W 1/16 sec. cor. of sec. 28 only, is at midpoint bet. the closing cor. of secs. 28 and 29 and the 1/4 sec. cor. of sec. 28 only, on the S. bdy. of sec. 28.

From this point, the W 1/16 sec. cor. of sec. 28 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears S. 27 3/4° W., 0.03 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true point

Reset the iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 28

1984

from which the bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 8 ins. diam., bears N. 44° E.,
20 1/2 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 2 1/2 ° W.,
52 lks. dist., with healed blaze.

Descend over SW. slope.

53.70 Ravine, drains S.; asc. over SE. slope.

70.15 Spur, slopes S.; desc. over SW. slope.

72.72 The closing cor. of sec. 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 22 S R 9 W

CC

S 29 | S 28

S 33

1976

from which the bearing tree mkd. by Wofford, Rogers, and Chatters

A fir, 10 ins. diam., bears N. 28° W.,
25 lks. dist., with healed blaze.

No other suitable trees available.