

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S. R. 9 W. Willamette Meridian, Oregon

17025

CHAINS

From this point, United States Coast and Geodetic Survey triangulation station "HIGH POLE", bears, S. 47° 16' E., 4.48 chs. dist., monumented with a bronze disc, 3½ ins. diam., seated in the top of an iron pipe, 4 ins. diam., firmly set, in concrete, projecting 6 ins. above ground, mkd. HIGH POLE 1953.

Descend over broken SW. slope.

73.75 Dirt road, 20 lks. wide, bears S. 15° E. and S. 15° W.

75.60 Ravine, drains S. 35° W.; asc. along broken S. slope.

78.30 The cor. of secs. 32 and 33 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S R 9 W
S 29
S 32 | S 33

1975

from which the remains of an original bearing tree

A burned fir stump, 20 ins. diam., bears N. 36° W., 41 lks. dist., with axe marks visible on burned remains. (Record, 37 lks.)

and bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 18 ins. diam., bears S. 35° E., 9 lks. dist., with healed blaze.

A fir, 18 ins. diam. bears S. 89° W., 58 lks. dist., with healed blaze.

Land mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, oak, maple, and alder; undergrowth, fern, vine maple, salal, Oregon grape, poison oak, arrowwood, blackberry, and rhododendron.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 34' W., bet. secs. 21 and 28.

Ascend over E. slope, through heavy timber and dense undergrowth.

5.40 Ravine, drains N. 60° E.; asc. over E. slope.

8.20 Spur, slopes N. 30° E.; desc. over W. slope.

10.70 Ravine, drains N. 20° E.; asc. over NE. slope.

15.40 Spur, slopes N. 10° W.; desc. over SW. slope.

21.455 Point for the E 1/16 sec. cor. of secs. 21 and 28.