

County Surveyor's Record, Douglas County, Oregon

17926

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

From this point, the E 1/16 sec. cor. of secs. 21 and 28, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears N. 81° 42' W., 0.095 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	R 9 W	
	S 21	
E 1/16		S 28

1984

from which the bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 21 ins. diam., bears N. 22¼° E.,
48 ½ lks. dist., with healed blaze.

A fir, 51 ins. diam., bears S. 66½° E.,
116 lks. dist., with healed blaze.

Descend over SW. slope.

26.60 Creek, 2 lks. wide, course N. 65° W.; desc. over NW. slope.

28.10 Creek, 10 lks. wide, course N. 10° W.; asc. over NE. slope.

40.66 The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S	R 9 W	
¼	S 21	
		S 28

1975

from which the remains of the original bearing trees

A fir, 57 ins. diam., bears N. 11° E.,
55 lks. dist., with illegible scribe marks
visible on open blaze. (Record, N. 15° E.)

A fir snag, 42 ins. diam., bears S. 22 ½° E.,
31 lks. dist., with healed blaze.

and a new bearing tree

A fir, 13 ins. diam., bears S. 48 ¼° W.,
37 lks. dist., mkd. ¼ S28 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, oak, maple, and alder;
undergrowth, fern, arrowwood, salal, Oregon grape,
rhododendron, poison oak, and blackberry.