

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T 22 S R 9 W Willamette Meridian, Oregon

17027

CHAINS

From the cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 22 S	R 9 W
S 20	S 21
S 29	S 28

1975

from which the remains of the original bearing trees

A fir, 30 ins. diam., bears N. 8° E.,
49 lks. dist., with healed blaze.

A fir stump, 28 ins. diam., bears S. 8° E.,
64 lks. dist., with old axe marks visible
on decayed blaze. (Record, 72 lks.)

A root hole, bears S. 71° W., 73 lks.
dist., with a downed fir, 44 ins. diam.,
alongside, with illegible scribe marks
visible on decayed blaze.

and the bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 11 ins. diam., bears S. 15 ¼° E.,
19½ lks. dist., with healed blaze.
(Record, S. 1 ½° E., 29 lks.)

A hemlock, 10 ins. diam., bears S. 57° W.,
42 ½ lks. dist., with healed blaze.
(Record, S. 37°W., 36 lks.)

A fir, 23 ins. diam., bears N. 10 ¾° W.,
152 lks. dist., with healed blaze.
(Record, N. 13 ½° W., 144 lks.)

S. 0° 40' E., bet. secs. 28 and 29.

Descend over SW. slope, through heavy timber and dense undergrowth.

- | | |
|-------|---|
| 0.50 | Ravine, drains S. 60° W.; asc. over NW. slope. |
| 3.65 | Spur, slopes SW.; desc. over SE. slope. |
| 8.15 | Ravine, drains S. 65° W.; asc. over N. slope. |
| 11.75 | Spur, slopes W.; desc. over S. slope. |
| 15.40 | Gravelled road, 15 lks. wide, bears SE. and N 60° W., in curve. |
| 16.40 | Creek, 1 lk. wide, course N. 40° W.; asc. over NE. slope. |
| 20.15 | Creek, 1 lk. wide, course N. 40° E., asc. over NW. slope. |
| 20.80 | Gravelled road, 15 lks. wide, bears NE. and SW. |
| 35.50 | Same gravelled road, 15 lks. wide, bears N. 30° W. and E. |