

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

17029

CHAINS

Ascend over NE. slope

67.20 Ridge, bears N. 75° E. and S. 50° W.; desc. over SW. slope.

71.54 The original closing cor. of secs. 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

AM	
S 29	S 28
S 33	

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 60° E., 63 lks. dist., no marks visible.

A sawed fir stump, 60 ins. diam., bears N. 61° W., 12 lks. dist., with scribe marks T2 visible on open blaze.

Descend over SW. slope.

71.99 The closing cor. of secs. 28 and 29, hereinbefore described.

From the cor. of secs. 6 and 7 only, on the W. bdy. of sec. 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S	R 9 W
S 6	S 8
S 7	
1970	

from which the remains of the original bearing trees

A decayed fir stump, 20 ins. diam., bears N. 57° E., 62 lks. dist., no marks remaining. (Record, 66 lks. dist.)

A decayed fir stump, 22 ins. diam., bears S. 65° E., 48 lks. dist., no marks visible on decayed blaze.

A fir, 38 ins. diam., bears S. 58° W., 57 lks. dist., with healed blaze and an X on the bark at breast height.

A root hole, bears N. 54½° W., 171 lks. dist., with a downed fir, 44 ins. diam., alongside, no marks visible on decayed blaze.

and the remains of bearing trees mkd. by person (s) unknown

A fir snag, 19 ins. diam., bears N. 60° E., 15 lks. dist., with no marks visible on open blaze.

A fir, 13 ins. diam., bears S. 80 ½° W., 29 lks. dist., with healed blaze at breast height.