

County Surveyor's Record, Douglas County, Oregon

17⁰30

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Jelley

A fir, 16 ins. diam., bears N. 50½° W.,
39 lks. dist., with healed blaze.

N. 0° 10' W., on the E. bdy. of sec. 6.

Ascend over S. slope, through moderate timber and undergrowth.

2.50 Spur, slopes E.; desc. over NE. slope.

4.10 True point for the closing cor. of secs. 5 and 8, hereinafter described.

Descend over NE. slope.

5.30 Creek, 3 lks. wide, course S. 70° E.; asc. over broken SE. slope.

22.85 Spur, slopes E.; desc. along broken E. slope.

36.20 Creek, 5 lks. wide, course N. 80° E.; asc. over SE. slope.

38.00 Spur, slopes S. 75° E.; desc. over NE. slope.

38.85 Creek, 2 lks. wide, course S. 75° E.; asc. over SE. slope.

39.86 The ¼ sec. cor. of sec. 6 only, determined from the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears
S. 73° E., 18 lks. dist., with scribe marks
4 S visible on decayed blaze.

From this point, the ¼ sec. cor. of sec. 6 only, erroneously reestablished by Wofford, Rogers, and Chatters, in 1973-79, bears S. 4° E., 0.072 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S R 9 W
¼ S 6 |
1983

from which the bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 23 ins. diam., bears S. 78 ½° W.,
89½ lks. dist., with healed blaze.
(Record, S. 83° W., 89 lks.)

A fir, 31 ins. diam., bears N. 85 ¼° W.,
63½ lks. dist., with healed blaze.
(Record, N. 79° W., 65 lks.)