

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
 Portion of the Subdivisional Lines,
 T. 22 S., R 9 W., Willamette Meridian, Oregon

17931

CHAINS

N. 0° 50' W., beginning new measurement.

Ascend over S. slope.

2.15 Spur, slopes E.; desc. over NE. slope.

3.76 Point for the ¼ sec. cor. of sec. 5 only, at proportionate dist. on the W. bdy. of sec. 5.

From this point the ¼ sec. cor. of sec. 5 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears South, 0.255 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
 | ¼ S 5
 1983

from which bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 44 ins. diam., bears N. 18½° E.,
 93 lks. dist., with healed blaze.

A hemlock, 14 ins. diam., bears S. 19 ½° E.,
 95 lks. dist., with scribe marks ¼ S5 BT
 visible on partially healed blaze.

Continue descent over NE. slope.

15.15 Creek, 3 lks. wide, course S. 30° E.; asc. over SW. slope.

19.87 Point for the N 1/16 sec. cor. of sec. 6 only.

From this point, the N 1/16 sec. cor. of sec. 6 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears S. 6° 29' W., 0.044 chs. dist., monumented with an iron post, 2½ ins. diam., loosely set, in a mound of stone, 4 ft. base, to top, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
 N 1/16 |
 S 6 |
 1983