

County Surveyor's Record, Douglas County, Oregon

17032

Corrective Dependent Resurvey,
Portion of the Subdivisional Lines,
T. 22 S., R 9 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. by Wofford, Rogers and Chatters

A maple, 18 ins. diam., bears S. $27 \frac{1}{2}^{\circ}$ W.,
66 $\frac{1}{2}$ lks. dist., with scribe marks 1/16 S6 BT
visible on partially healed blaze.

A maple, 13 ins. diam., bears N. 60° W.,
37 lks. dist., with scribe marks 1/16 S6 BT
visible on partially healed blaze.

Ascend over SW. slope.

23.53

Point for the N 1/16 sec. cor. of sec. 5 only, at proportionate dist. on the W. bdy. of sec. 5.

From this point the N 1/16 sec. cor. of sec. 5 only, erroneously established by Wofford, Rogers, and Chatters, in 1973-79, bears S. $7^{\circ} 42'$ E., 0.075 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

Remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

```

T 22 S   R 9 W
      |   N 1/16
      |   S 5
      |   1983
    
```

from which the bearing trees mkd. by Wofford, Rogers, and Chatters

A triple maple, 13 ins. diam., bears N. 80° E.,
22 $\frac{1}{2}$ lks. dist., with healed blaze.

A fir, 23 ins. diam., bears S. $40 \frac{1}{2}^{\circ}$ E.,
64 lks. dist., with healed blaze.

Continue over broken SW. slope.

37.67

The closing cor. of secs. 5 and 6, on the S. bdy. of sec. 31, T. 21 S., R. 9 W., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

```

T 21 S   R 9 W
      |   S 31
      |-----|
      |   S 6   |   S 5
      |   CC     |
      |   T 22 S R 9 W
      |   1977
    
```

from which bearing trees mkd. by Wofford, Rogers, and Chatters