

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
 Portion of the Subdivisional Lines,
 T. 22 S., R. 9 W., Willamette Meridian, Oregon 17933

CHAINS

A fir, 25 ins. diam., bears S. 40° E.,
 57 lks. dist., with healed blaze.
 (Record, S. 38° E., 56 lks. dist.)

A fir, 30 ins. diam., bears S. 4° W.,
 35 lks. dist., with healed blaze.
 (Record, S. 8½° W.)

From this point, the original closing cor. of secs. 5
 and 6, bears N. 0° 50' W., 0.200 chs. dist.,
 monumented with an iron post, 2 ins. diam., firmly set,
 projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 21 S	
BLM	S 31	R
1977	S 6 S 5 9	
AM	T 22 S	W
	CC	

1971

from which the remains of the original bearing trees

A root hole, bears S. 2° E., 307 lks. dist.,
 with a downed fir, 36 ins. diam., alongside,
 no marks visible on decayed blaze.

A decayed fir stump, size indeterminate, bears
 S. 27 ½° W., 90 lks. dist., no marks
 visible on decayed blaze.

A decayed fir stump, size indeterminate, bears
 N. 17° W., 65 lks. dist., with scribe marks
 BT visible on decayed blaze.

and bearing trees mkd. by John M. Powell, Deputy County
 Surveyor, in 1971

A fir, 11 ins. diam., bears S 26° E.,
 27 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 61° W.,
 16 lks. dist., with healed blaze.

From this same point, the cor. of secs. 31 and 32 only,
 T. 21 S., R. 9 W., bears S 89° 53' E., 3.11 chs.
 dist., monumented with an iron post, 2 ins. diam.,
 firmly set, projecting 8 ins. above ground, with brass
 cap mkd.

COUNTY SURVEYORS OFFICE

	T 21 S	
S 31		S 32 R
	S 5	9
T 22 S		W
	CC	

1971

from which the remains of the original bearing trees

A fir, 55 ins. diam., bears S. 73° E.,
 195 lks. dist., with healed blaze.