

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey,
 Portion of the Subdivisional Lines,
 T. 22 S., R. 9 W., Willamette Meridian, Oregon

17034

CHAINS

A fir stump, 20 ins. diam., bears S. 44° W.,
 54 lks. dist., with healed blaze.

A decayed fir stump, size indeterminate, bears
 N. 81° W., 257 lks. dist., no marks visible.

and bearing trees mkd. by John M. Powell, Deputy County
 Surveyor, in 1971

A fir, 22 ins. diam., bears N. 83° E.,
 33 ½ lks. dist., with healed blaze.

A fir, 10 ins. diam. bears S 21° E.,
 23 lks. dist., with healed blaze..

a fir, 22 ins. diam., bears N. 13 ° W.,
 37½ lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, oak, maple, and alder;
 undergrowth, fern , vine maple, salal, Oregon grape,
 poison oak, blackberry, thimbleberry, and rhododendron.

Dependent Resurvey of a portion of the West Boundary,
 T. 22 S., R. 9 W., Willamette Meridian, Oregon.

(Restoring the survey by Aurelius Todd, in 1894,
 the survey by Alonzo Gesner, in 1894,
 the survey by Alonzo Gesner and E. O. Worrick, in 1894,
 the resurvey by Fred Mensch, Charles M. Collier,
 Fred. W. Rodolf, Elmer F. Strickler, and
 Gerald A. Sorrels, in 1919, and
 the resurvey by Harvey E. Wofford, Wayne L. Rogers,
 and Owen C. Chatters, II, in 1973-79)

From the cor. of secs. 1 and 12 only, T. 22 S.,
 R. 10 W., determined from the remaining original
 bearing tree

A cedar, 70 ins. diam., bears S. 3° W.,
 6 lks. dist., with axe marks visible on decayed
 blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam.,
 24 ins. in the ground, with brass cap mkd.

T 22 S	T 22 S
S 1	R 9 W
S 12	S 7
R 10 W	

1983

from which a new bearing tree

A cedar, 68 ins. diam., bears N. 21° W.,
 69 lks. dist., mkd. T22S R10W S1 BT.