

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the West Boundary
T. 22 S., R. 9 W., Willamette Meridian, Oregon

1935

CHAINS

N. 1° 16' E., on the E. bdy. of sec. 1, T. 22 W.,
R. 10 W., marking and blazing the true line.

Ascend over SE. slope, through heavy timber and
moderate undergrowth.

1.55 Top of ascent, slopes E.; desc. over NE. slope.

2.24 Point for the closing cor. of secs. 6 and 7, herein-
after described.

The corner is located at bottom of descent, slopes E.;
asc. over SE. slope.

3.60 Top of ascent, slopes E.; desc. over NE. slope.

6.15 Creek, 1 lk. wide, course S. 60° E.; asc. over
SE. slope.

11.70 Spur, slopes E.; desc. over NE. slope.

12.50 Creek, 1 lk. wide, course E.; asc. over SE. slope.

25.95 Spur, slopes S. 60° E.; desc. over NE. slope.

31.85 Little Mill Creek, 15 lks. wide, course S. 25° E.;
asc. over SW. slope.

38.07 The $\frac{1}{4}$ sec. cor. of sec. 1 only, T. 22 S., R. 10 W.,
monumented with a brass tablet, $3\frac{1}{2}$ ins. diam.,
firmly set, in a sandstone boulder, 20 x 8 x 2 ft.,
above ground, mkd. $\frac{1}{4}$ S1 on W. face. The brass tablet
is mkd.

T 22 S
R 10 W
 $\frac{1}{4}$ |
S1 |

1974

from which an original bearing tree

A fir, 68 ins. diam., bears S. 34° W.,
76 lks. dist., no marks visible on open
blaze. (Record, S. 45° E.)

and bearing tree reported by Wofford, Rogers, and
Chatters

A fir, 55 ins. diam., bears N. 64° E.,
25 lks. dist., with healed blaze.
(Record, 30 lks. dist.)

and bearing trees mkd. by Wofford, Rogers, and Chatters

A fir, 18 ins. diam., bears S. 10° W.,
58 lks. dist., with healed blaze.
(Record, S. 13° W.)

A fir, 25 ins. diam., bears N. 35° W.,
26 lks. dist., with healed blaze.

N. 0° 36' W., beginning new measurement.