

County Surveyor's Record, Douglas County, Oregon

17936

Dependent Resurvey, Portion of the West Boundary
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- Ascend over SW. slope.
- 3.86 Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, hereinafter described.
- Ascend over SW. slope.
- 5.45 Spur, slopes N. 55° W.; desc. over NW. slope.
- 12.70 Little Mill Creek, 12 lks. wide, course S. 75° W.; asc. over SE. slope.
- 20.20 Top of ascent, slopes E.; desc. over NE. slope.
- 21.50 Creek, 4 lks. wide, course S. 40° E.; asc. over SE. slope.
- 40.95 The closing cor. of T. 21 S., R. 10 W. and T. 22 S., R. 9 W., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

	T 22 S	T 21 S	
	R 10 W	R 10 W	
	S 1	S 36	C
		S 6	
		R 9 W	C
		T 22 S	

1974

from which bearing trees mkd. by Wofford, Rogers, and Chatters

A cedar, 22 ins. diam., bears N. 32° E.,
23 lks. dist., with scribe marks R10W S 36
CC BT visible on partially healed blaze.

A hemlock, 13 ins. diam., bears S. 42° E.,
87 lks. dist., with healed blaze.

From this point, the angle point, on the E. bdy. of
T. 22 S., R. 10 W., bears N. $0^\circ 36' W.$, 0.30 chs.
dist., monumented with a sandstone boulder, 8 x 8 x 5
ft. above ground, with chisel mark x visible on N.
face, from which the bearing trees mkd. by Wofford,
Rogers, and Chatters

A fir, 46 ins. diam., bears S. $31\frac{1}{4}^\circ W.$,
184 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. $44\frac{1}{2}^\circ W.$,
37 lks. dist., with healed blaze.

From this same point, United States Coast and Geodetic
Survey Triangulation Station "FERNTOP" bears
N. $57^\circ 26' 25'' E.$, 180.925 chs. dist., monumented
with an iron post, 4 ins. diam., firmly set, projecting
6 ins. above ground, with brass cap mkd. FERNTOP 1952
and a triangle.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, and maple;

Undergrowth, vine maple, salal, fern, blackberry, and
salmonberry.