

# County Surveyor's Record, Douglas County, Oregon

17038

Dependent Resurvey of  
Portion of the Subdivisional Lines,  
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

N. 0° 21' W., bet. secs. 20 and 21.

Ascend over SW. slope, through heavy timber and dense undergrowth.


1.50 Spur, slopes S. 75° W.; desc. over NW. slope.

18.10 Ravine, drains W.; asc. over SW. slope.

33.65 Spur, slopes S. 70° W.; asc. along W. slope.

35.50 Spur, slopes N. 20° W.; desc. over NE. slope.

38.12 The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees

A fir, 55 ins. diam., bears S. 52° E.,  
114 lks. dist., with scribe marks BT  
visible on open blaze.

A decayed fir snag, size indeterminate,  
bears S. 31° W., 28 lks. dist., no marks  
visible.

and a bearing tree mkd. by Wofford, Rogers, and Chatters

A fir, 23 ins. diam., bears N. 55  $\frac{1}{2}$ ° W.,  
52  $\frac{1}{2}$  lks. dist., with healed blaze.  
(Record, 54 lks.)

---

North, beginning new measurement.

Descend over NE. slope.

8.50 Top of rock bluff, 40 ft. high, edge bears S. 60° E.  
and N. 60° W.

12.35 Ravine, drains S. 50° E.; desc. along E. slope.

23.95 Spur, slopes NE.; desc. over NE. slope.

25.30 Gravelled road, 15 lks. wide, bears N. 70° W. and  
S. 70° E.

34.90 Ravine, drains E.; desc. along broken E. slope.

37.40 Spur, slopes E; desc. over NE. slope.

38.97 The cor. of secs. 16, 17, 20, and 21, monumented with  
an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, projecting  
10 ins. above ground, with brass cap mkd.