

County Surveyor's Record, Douglas County, Oregon

17042

Dependent Resurvey of
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

An alder, 8 ins. diam., bears N. 89 1/4° E.,
11 1/2 lks. dist., mkd. T22S R9W S5 CC BT.

An alder, 13 ins. diam., bears S. 43° E.,
21 1/2 lks. dist., mkd. T22S R9W S8 CC BT.

From this same point the original closing cor. of
secs. 5 and 8 bears S. 89° 49' W., 0.068 chs. dist.
determined from the remains of an original bearing tree

A fir stump, size indeterminate, bears
N. 31 1/2° E., 23 lks. dist., with
scribe marks S5 visible on opened blaze.

From this same point, the cor. of secs. 6 and 7 only,
bears S. 0° 10' E., 4.10 chs. dist., hereinbefore
described.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock cedar, maple and alder; undergrowth, vine
maple, Oregon grape, blackberry, rhododendron, poison oak, salal,
and fern.

From the cor. of secs. 6 and 7 only, on the W. bdy. of
sec. 8.

N. 89° 38' W., bet. secs. 6 and 7.

Ascend over broken E. slope.

27.60 Top of ascent, slopes SE.; desc. over SW. slope.

29.05 Ravine, drains S. 35° E.; asc. over SE. slope.

39.95 Point for the 1/4 sec. cor. of secs. 6 and 7, at
proportionate dist.; there is no remaining evidence of
the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
1/4 S 6
 S 7

1982

from which

A fir, 26 ins. diam., bears N. 80 3/4° E.,
56 1/2 lks. dist., mkd. 1/4 S6 BT.

A fir, 30 ins. diam., bears S. 14 1/2° E.,
27 lks. dist., mkd. 1/4 S7 BT.

Continue ascent over SE. slope.

51.60 Spur ridge, bears N. 35° E. and S. 35° W.; desc.
over broken NW. slope.

56.30 Head of ravine, drains N. 25° W., asc. over NE. slope.

59.50 Rocky spur, slopes N. 30° W.; desc. over SW. slope.