

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of
Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

17043

CHAINS

69.00 Leave timber, edge bears N. and S.; continue across rock bluff, slopes SW.

72.50 Leave rock bluff; enter timber, edge bears NE. and SW.

88.00 Little Mill Creek, 12 lks. wide, course S. 30° W.; asc. over E. slope.

90.56 The closing cor. of secs. 6 and 7, monumented with the original sandstone, 18 x 25 x 7 ins., firmly set, 6 ins. in the ground, mkd. CC on the E., 1 notch on the N., and 5 notches on the S. edges, from which the remains of the original bearing trees

- A fir snag, 68 ins. diam., bears N. 48° E., 118 lks. dist., with healed blaze.
- A decayed fir stump, size indeterminate, bears S. 50° E., 42 lks. dist., no marks remaining. (Record, 43 lks.)
- A root hole, bears S. 68° W., 56 lks. dist., with a downed hemlock, 30 ins. diam., alongside, with healed blaze.

Add the marks AM to the top of the stone and bury in place.

90.99 Intersect the E. bdy. of sec. 1, T. 22 S., R. 10 W., True point for the closing cor. of secs. 6 and 7.

Sat an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	T 22 S	
S 1	S 6	CC
	S 7	
R 10 W	R 9 W	
1983		

from which

- A hemlock, 23 ins. diam., bears N. 44 ½° E., 69 lks. dist., mkd T22S R9W S6 CC BT.
- A fir, 90 ins. diam., bears S. 41° E., 58 lks. dist., mkd. T22S R9W S7 CC BT.

From this point, the cor. of secs. 1 and 12 only, T. 22 S., R. 10 W., bears S. 1° 16' W., 2.24 chs. dist., hereinbefore described.

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, hemlock, maple, and alder; undergrowth, vine maple, salal, fern blackberry, and salmonberry.

The point for the ¼ sec. cor. of sec. 6 only, T. 22 S., R. 9 W., at proportionate dist., on the W. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.