


County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 6,
T. 22 S., R. 9 W., Willamette Meridian, Oregon 1945

CHAINS



from which


A fir, 35 ins. diam., bears S. 50° E.,
31 lks. dist., mkd. CN 1/16 S6 BT.

A fir, 42 ins. diam., bears S. 54° W.,
21 lks. dist., mkd. X BT.

Continue ascent along E. slope.

65.90 Top of ascent, slopes E.; desc. over NE. slope.

77.32 The $\frac{1}{4}$ sec. cor. of sec. 6 only, on the N. bdy. of the
tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam.,
firmly set, projecting 8 ins. above the ground, with
brass cap mkd.



from which bearing trees mkd. by Wofford, Rogers, and
Chatters

A fir, 20 ins. diam., bears S. 57 $\frac{3}{4}$ ° E.,
56 $\frac{1}{2}$ lks. dist., with healed blaze.
(REcord, S. 56 $\frac{1}{4}$ ° E.)

A fir, 16 ins. diam., bears S. 59 $\frac{1}{2}$ ° W.,
95 lks. dist., with healed blaze.
(Record, West)

From the $\frac{1}{4}$ sec. cor. of sec. 6 only, on the E. bdy.
of sec. 6.

N. 89° 45' W., on the E. and W. center line of sec. 6.

Ascend over broken SE. slope.

3.80 Creek, 2 lks. wide, course S. 75° E.; asc. over
NE. slope.

8.70 Spur, slopes S. 50° E.; desc. over SW. slope.

20.11 Point for the center E 1/16 sec. cor. of sec. 6, is
located in small creek, 2 lks. wide, course
S. 30° E., where it is impracticable to establish a
permanent monument.

Ascend over NE. slope.

20.41 Point selected for witness cor. to the center
E 1/16 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam.,
24 ins. in the ground, with brass cap mkd.