

County Surveyor's Record, Douglas County, Oregon

17953

T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and subdivision of sections 3 and 11, Township 27 South, Range 3 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The north boundary of the township was surveyed by Addison R. Flint, U.S. Deputy Surveyor, in 1855.

A portion of the subdivisional lines was surveyed by Addison R. Flint and L. L. Williams, U. S. Deputy Surveyors, in 1871.

The remaining portion of the subdivisional lines was surveyed by Samuel C. Flint, U. S. Deputy Surveyor, in 1882.

A portion of the north boundary of the township and subdivisional lines was resurveyed by Harold D. Corbin, Cadastral Surveyor, in 1958.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated December 12, 1983, for Group No. 1189, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes were given herein. Only those lines bounding or crossing public lands were blazed.

The geographic position of the center East 1/16 section cor. of section 3, as determined from a direct tie to Douglas County, Horizontal Control Station "JIM", is as follows:

Latitude 43° 14' 59.3" N. Longitude 123° 02' 01.6" W.

The mean magnetic declination is 20° 00' E.

Dependent Resurvey of
A Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the surveys by Addison R. Flint, in 1855 and 1871, the survey by Samuel C. Flint, in 1882, and the dependent resurvey by Harold D. Corbin, in 1958)

Beginning at the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.