

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, 17955  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 26 ins. diam., bears S. 77° W.,  
28 lks. dist., with healed blaze.

and the remains of a bearing tree mkd. by Ben B. Irving, County Surveyor, in 1945

A fir stump, 42 ins. diam., bears N. 80½° E.,  
47 lks. dist., no marks visible.

and bearing trees mkd. by Corbin

A hemlock, 17 ins. diam., bears S. 71 3/4° E.,  
65 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears S. 11½° W.,  
57 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, oak, pine, and maple; undergrowth, hazel, vine maple, poison oak, salal, and Oregon grape.

From the cor. of secs. 11, 12, 13, and 14.

N. 89° 08' W., bet. secs. 11 and 14.

Descend over SW. slope, through heavy timber and dense undergrowth.

20.95

The E 1/16 sec. cor. of secs. 11 and 14, established and recorded by Ben B. Irving, County Surveyor, in 1945, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by Irving

A fir, 20 ins. diam., bears N. 82° W.,  
23 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16  $\frac{S\ 11}{S\ 14}$

1984

from which a new bearing tree

A fir, 16 ins. diam., bears S. 7½° W.,  
8 lks. dist., mkd. E 1/16 S14 BT.

Deposit the iron pipe alongside the iron post.

N. 89° 16' W., beginning new measurement.

Descend over SW. slope.

8.40

Cavitt Creek Road, paved, 30 lks. wide, bears N. 10° E. and S. 5° W.