

County Surveyor's Record, Douglas County, Oregon

17956

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

10.20 Cavitt Creek, 60 lks. wide, course N. 20° W.; asc. over NE. slope.

11.65 Gravelled road, 25 lks. wide, bears N. 30° W. and S. 10° E.

20.89 The ¼ sec. cor. of secs. 11 and 14, perpetuated and recorded by Ben B. Irving, County Surveyor, in 1945, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above the ground.

from which the original bearing trees

A cedar, 41 ins. diam., bears S. 41¼° W.,
48 lks. dist., with fragmentary scribe marks
visible on opened blaze. (Record, S. 25° W.)

A cedar, 53 ins. diam., bears N. 61¼° W.,
18 lks. dist., with fragmentary scribe marks
visible on opened blaze. (Record, N. 45° W.,
14 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 3 W
¼ $\frac{S 11}{S 14}$
1984

Deposit the iron pipe alongside the iron post.

Corner is located at intersection of fences, extending N., S., and E.

S. 88° 05' W., beginning new measurement.

Ascend over broken NE. slope.

42.09 The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

Fd. OK 6/2006	T 27 S R 3 W
D. Edwards	$\frac{S 10 S 11}{S 15 S 14}$
M150-67	1958

from which the remains of the original bearing trees

A fir, 30 ins. diam., bears S. 68° E.,
19 lks. dist., with healed blaze.

A root hole, with down fir alongside,
44 ins. diam., bears N. 38° W., 54 lks.
dist., no marks visible.

and bearing trees mkd. by Ben B. Irving, County Surveyor, in 1945

A cedar, 21 ins. diam., bears N. 66° E.,
43½ lks. dist., with healed double blaze.