

# County Surveyor's Record, Douglas County, Oregon

17958 Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

- Ascend over SE. slope, through scattering timber and dense undergrowth.
- 6.60 Ridge, bears E. and W.; desc. over NE. slope.
- 12.90 Creek, 4 lks. wide, course E.; asc. over SE. slope.
- 33.10 Spur, slopes E.; desc. over NE. slope.
- 38.25 Creek, 5 lks. wide, course E.; asc. over SE. slope.
- 39.44 The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

FD OK  
BY Ronald  
Geisler  
2/87 M103-61

T 27 S R 3 W  
¼  
S 3 | S 2  
1958

FD OK BY  
B. Shaner  
2/95  
M 121-49

from which the remaining original bearing tree

A fir, 20 ins. diam., bears N. 80° E., 71 lks. dist., with opened blaze, no marks visible.

and the remains of bearing trees mkd. by James Byron Deputy County Surveyor, in 1954

A yew, 7 ins. diam., bears S. 49° E., 46 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir stump, 10 ins. diam., bears S. 76½° W., 163½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and bearing trees mkd. by Corbin

A cedar, 11 ins. diam., bears N. 74½° E., 94 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 41 ins. diam., bears S. 39° W., 99 lks. dist., with healed blaze.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, hemlock, madrone, and oak; undergrowth, poison oak, salal, and Oregon grape.

From the cor. of secs. 2, 3, 10, and 11.

S. 86° 41' W., bet. secs. 3 and 10.

Descend over SW. slope, through scattering timber and dense undergrowth.

- 14.50 Ravine, drains S. 20° E.; asc. over SE. slope.
- 30.05 Spur, slopes S. 25° W.; desc. over SW. slope.
- 39.70 Creek, 3 lks. wide, course S. 10° E.; asc. over broken SE. slope.
- 41.30 The 1/4 sec. cor. of secs. 3 and 10, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.