

County Surveyor's Record, Douglas County, Oregon

17960 Dependent Resurvey, Portion of the Subdivisional Lines,

T. 27, S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A fir, 18 ins. diam., bears S. $51\frac{1}{2}^{\circ}$ E.,
59 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ W.,
43 lks. dist., with healed blaze.

A fir stump, 18 ins. diam., bears N. $67\frac{1}{4}^{\circ}$ W.,
67 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, oak, and maple;
undergrowth, vine maple, hazel, poison oak, salal,
ocean spray, and blackberry.

N. $2^{\circ} 01'$ E., bet. secs. 3 and 4.

Ascend over SW. slope, through scattering timber and
moderate undergrowth.

20.33

The S $1/16$ sec. cor. of secs. 3 and 4, monumented with
an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting
4 ins. above ground, with brass cap mkd.

	S $1/16$	
S 4		S 3
	1958	

from which the remains of a bearing tree mkd. by Corbin

A fir snag, 14 ins. diam., bears N. 4° W.,
69 lks. dist., with scribe marks S $1/16$ S4 BT
visible on partially healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. $77\frac{1}{2}^{\circ}$ E.,
 $45\frac{1}{2}$ lks. dist., mkd. S $1/16$ S3 BT.

A fir, 6 ins. diam., bears S. 77° W.,
 $4\frac{1}{2}$ lks. dist., mkd. S $1/16$ S4 BT.

N. $2^{\circ} 30'$ E., beginning new measurement.

Ascend over SW. slope.

3.25

Ridge, bears NW. and SE.; desc. over NE. slope.

20.32

The $1/4$ sec. cor. of secs. 3 and 4, monumented with an
iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 5 ins.
above ground, with brass cap mkd.

T 27 S	R 3 W	
	↓	
S 4		S 3
	1958	

from which bearing trees mkd. by Corbin

A white fir, 16 ins. diam., bears S. 16° E.,
73 lks. dist., with healed blaze.