

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines 17961
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A cedar, 14 ins. diam., bears N. 45½° W.,
54 lks. dist., with healed blaze.

N. 1½ 57' E., beginning new measurement.

Descend over NE. slope.

21.15 Foot of descent, slopes E.; asc. over E. slope.

41.68 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 26 S	R 3 W
S 33	S 34
S 4	S 3

T 27 S

1958

from which the remains of the original bearing trees

A fir stump, 48 ins. diam., bears N. 78° E.,
54 lks. dist., with fragmentary scribe marks
visible on opened blaze.

A fir stump, 40 ins. diam., bears S. 78° W.,
50 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Corbin

A cedar, 15 ins. diam., bears N. 32 ¾° E.,
47 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

A fir, 10 ins. diam., bears S. 47¼° E.,
15 lks. dist., with healed blaze.

A fir snag, 11 ins. diam., bears S. 68° W.,
17 lks. dist., with healed blaze.

A root hole, with down fir alongside, 12 ins.
diam., bears N. 45° W., 17 lks. dist., with
scribe marks T26S R3 S33 visible on partially
healed blaze.

and new bearing trees

A pine, 5 ins. diam., bears S. 12° W., 40 lks.
dist., mkd. X BT.

A cedar, 13 ins. diam., bears N. 88° W., 52½ lks.
dist., mkd. T26S R3W S33 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, oak, maple, and
madrone; undergrowth, poson oak, hazel, salal, vine
maple, and Oregon Grape.

Subdivision of Section 3,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 3 and 10.