

County Surveyor's Record, Douglas County, Oregon

17962

Subdivision of Section 3,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS


N. 1° 06' E., on the N. and S. center line of sec. 3, marking and blazing the true line.

Ascend over SE. slope, through scattering timber and moderate undergrowth.

12.30 Gravelled road, 15 lks. wide, bears N. 70° E. and S. 70° W.

20.61 Point for the center S 1/16 sec. cor. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

A fir, 25 ins. diam., bears S. 40½° E., 12½ lks. dist., mkd. CS 1/16 S3 BT.

A cedar, 12 ins. diam., bears N. 30½° W., 22 lks. dist., mkd. CS 1/16 S3 BT.


Ascend over SE. slope.

25.30 Ridge, bears S. 70° E. and S. 60° W.; desc., over NE. slope.

38.20 Slope changes to broken NW. slope.

41.22 Point for the center ¼ sec. cor. of sec. 3, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A yew, 12 ins. diam., bears S. 42 ¾° W., 95 lks. dist., mkd. C 1/4 S3 BT.

A fir, 4 ins. diam., bears N. 63 ¾° W., 43 lks. dist., mkd. X BT.

Descend over broken NW. slope.

51.00 Gravelled road, 15 lks. wide, bears N. 35° E. and S. 35° W.

74.75 Ravine, drains N. 55° E.; asc. over broken SE. slope.

82.07 The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, in mound of stone, 3 ft. base, to top, with brass cap mkd.