

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 3,  
T. 27 S., R. 3 W. Willamette Meridian, Oregon

17965

**CHAINS**

From the center W 1/16 sec. cor. of sec. 3.

N. 1° 32' E., on the N. and S. center line of the NW 1/4 of sec. 3.

Descend over broken N. slope.

14.85 Dirt road, 15 lks. wide, bears N. 15° W., and S. 20° E.

18.70 Ravine, drains N. 55° E.; desc. over NE. slope.

20.05 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.

34.20 Creek, 4 lks. wide, course N. 20° E.; asc. over SE. slope.

41.29 The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

S 34  
S 1/16 ———  
S 3  
1958

from which bearing trees mkd. by Corbin

A fir, 15 ins. diam., bears S. 25¼° E., 15 lks. dist., with healed blaze.

A cedar, 10 ins. diam., bears N. 32° W., 38 lks. dist., with healed blaze.

and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966

A cedar, 16 ins. diam., bears N. 24° W., 53 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

Subdivision of Section 11,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 11 and 14.

N. 2° 45' E., on the N. and S. center line of sec. 11, marking and blazing the true line.

Ascend along broken E. slope, through heavy timber and dense undergrowth.

13.50 Creek, 3 lks. wide, course S. 40° E.; asc. along broken E. slope.

32.55 Spur, slopes N. 80° E.; desc. over broken NE. slope.

39.29 The center 1/4 sec. cor. of sec. 11, established and recorded by Ben B. Irving, Deputy County Surveyor, in 1945, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 14 ins. above ground, from which a bearing tree mkd. by Irving