

County Surveyor's Record, Douglas County, Oregon

17966

Subdivision of Section 11,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A yew, 12 ins. diam., bears N. 13° E.,
24 lks. dist., with scribe marks C $\frac{1}{4}$ S11
visible on partially healed blaze.

and a bearing tree mkd. by person(s) unknown

A maple, 18 ins. diam., bears S. 7 $\frac{1}{2}$ ° W.,
40 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 27 S R 3 W
C $\frac{1}{4}$
S 11
1984

N. 2° 29' E., beginning new measurement

Descend over broken NE. slope.

10.09

The center SN 1/64 sec. cor. of sec. 11, established
and recorded by Thomas E. Shrum, Jr., REgistered
Engineer, No. 4287, in 1964, and is accepted as the
corner, monumented with an iron pipe, 1 in. diam.,
firmly set, projecting 3 ins. above ground, with
aluminum cap mkd.

T 27 S R 3 W
S 11
CSN 1/64
4287

from which bearing trees mkd. by Shrum

A white oak, 15 ins. diam., bears N. 32 $\frac{1}{2}$ ° E.,
95 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 12° W., 43 lks.
dist., with healed blaze.

N. 2° 35' E., beginning new measurement.

Descend over broken NE. slope.

10.12

The center N 1/16 sec. cor. of sec. 11, established
and recorded by Ben B. Irving, Deputy County Surveyor,
in 1945, and perpetuated and recorded by Thomas E.
Shrum, Jr., Registered Engineer, No. 4287, in 1964, and
is accepted as the corner, monumented with an iron
pipe, 1 in. diam., firmly set projecting 2 ins. above
ground, with aluminum cap mkd.

T 27 S R 3 W
Sec. 11
CN 1/16
1964

from which a bearing tree mkd. by Irving