

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 11,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

17967

**CHAINS**

A white oak, 12 ins. diam., bears N. 70½° E.,  
59½ lks. dist., with fragmentary scribe  
marks visible on partially healed blaze.

and a bearing tree mkd. by person(s) unknown

A white oak, 12 ins. diam., bears S. 3° W.,  
27 lks. dist., with healed blaze.

N. 2° 40' E., beginning new measurement.

Descend over nearly level land.

0.95 Power line, 5 strands, bears S. 30° E. and N. 30° W.

1.15 Cavitt creek Road, paved, 30 lks. wide, bears N. 45° W.  
and S. 40° E.

2.35 Cavitt Creek, 60 lks. wide, course N. 50° W.; asc. over  
nearly level land.

10.04 The center NN 1/64 sec. cor. of sec. 11, established  
and recorded by Thomas E. Shrum, Jr., Registered  
Engineer, No. 4287, in 1964, and is accepted as the  
corner, monumented with an iron pipe, 1 in. diam.,  
firmly set, projecting 14 ins. above ground, with  
aluminum cap mkd.

T 27 S R 3 W  
Sec. 11  
CNN 1/64  
4287

from which bearing trees mkd. by Shrum

A fir, 19 ins. diam., bears N. 89° E.,  
94 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 39½° W.,  
179 lks. dist., with healed blaze.

N. 2° 44' E., beginning new measurement.

Descend over nearly level land.

4.35 Left bank of Little River, bears N. 70° E. and  
S. 70° W., course S. 70° W.

6.15 Right bank of Little River, bears N. 70° E. and  
S. 70° W.; asc. over nearly level land.

9.10 Little River Road, paved, 30 lks wide, bears N. 20° W.  
and S. 20° E.

10.07 The 1/4 sec. cor. of secs. 2 and 11, monumented with an  
iron post, 2½ ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd.

FD. OK 3/95  
BY BENTZ Vol 18  
Pg 41

T 27 S R 3 W  
S 2  
S 11  
1958

FD OK  
BY MARK S. GIBSON  
3/94 M.L.P. CA