

# County Surveyor's Record, Douglas County, Oregon

17968

Subdivision of Section 11,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

from which the remains of bearing trees mkd. by F. C. Frear, County Surveyor, in 1943

A cedar stump, 18 ins. diam., bears S. 86° E.,  
98 lks. dist., with scribe marks  $\frac{1}{4}$  S2 BT  
visible on partially healed blaze.

A white oak, 15 ins. diam., bears S. 8 $\frac{1}{2}$ ° W.,  
180 lks. dist., with healed double blaze.

and the remains of bearing trees mkd. by Corbin

A fir stump, 15 ins. diam., bears N. 19° E.,  
240 lks. dist., with healed blaze.  
(Record, 247 lks.)

A cedar stump, 20 ins. diam., bears S. 44 $\frac{1}{2}$ ° E.,  
201 lks. dist., with healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears S. 65 $\frac{1}{2}$ ° E.,  
38 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S11 BT.

A cedar, 11 ins. diam., bears N. 31 $\frac{1}{2}$ ° W.,  
50 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S2 BT.

From the  $\frac{1}{4}$  sec.cor. of secs. 11 and 12.

S. 89° 28' W., on the E. and W. center line of sec. 11.

Descend over NW. slope.

20.23

The center E 1/16 sec.cor. of sec. 11, established and recorded by Thomas E. Shrum, Jr., Registered Engineer, No. 4287, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 16 ins. above ground, with aluminum cap mkd.

T 27 S R 3 W  
Sec. 11  
CE 1/16  
RE 4287

from which bearing trees mkd. by Shrum

A yew, 16 ins. diam., bears S. 10° E.,  
50 lks. dist., with scribe marks CE 1/16  
S11 RE 4287 BT visible on opened blaze.

A white fir, 11 ins. diam., bears S. 60° W.,  
35 lks. dist., with healed blaze.

S. 89° 28' W., beginning new measurement.

Descend over NW. slope.

2.05

New Bridge Road, paved, 30 lks. wide, bears N. 25° E.,  
and S. 25° W.

9.65

Cavitt Creek, 60 lks. wide, course N. 15° E.; asc. over  
NE slope.

12.10

Cavitt Creek Road, paved, 30 lks. wide, bears S. and  
N. 10° W.