

County Surveyor's Record, Douglas County, Oregon

17970

Subdivision of Section 11,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
8.35	Spur, slopes S. 80° W.; desc. over broken NW. slope.
39.72	The center E 1/16 sec. cor. of sec. 11.
	<p>From the center W 1/16 sec. cor. of sec. 11.</p> <p>N. 3° 13' E., on the N. and S. center line of the NW¼ of sec. 11.</p> <p>Ascend along broken E. slope.</p>
15.30	Spur, slopes N. 75° E.; desc. over NW. slope.
17.30	Gravelled road, 20 lks. wide, bears S. 70° E. and S. 80° W., in curve.
20.17	<p>Point for the NW 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the NW¼</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 11 1984</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 78½° E., 35 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 54½° W., 31 lks. dist., mkd. NW 1/16 S11 BT.</p> <p>Descend over NW. slope.</p>
24.60	Jim Creek, 10 lks. wide, course N. 80° E.; asc. over S. slope.
26.60	Jim Creek Road, paved, 15 lks. wide, bears N. 80° E. and S. 80° W.
32.55	Spur, slopes S. 80° E.; desc. over NE. slope.
40.28	<p>The W 1/16 sec. cor. of secs. 2 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 S 1/16 ————— S 11 1958</p> <p>From which bearing trees mkd. by Corbin</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 63° E., 55 lks. dist., with healed blaze. (Record, yew, S. 65° E.)</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 51° W., 27 lks. dist., with healed blaze. (Record, fir)</p>
	From the center N 1/16 sec. cor. of sec. 11.