

County Surveyor's Record, Douglas County, Oregon

17974

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Howard W. Johnstone,
Registered Land Surveyor, No. 498, in 1970

A fir, 12 ins. diam., bears N. 60½° E., 28 lks.
dist. with healed blaze. (Record, N. 73° E.)

A fir, 19 ins. diam., bears S. 58 3/4° E., 6½ lks.
dist., with healed blaze. (Record, S. 47½° E.)

A fir, 22 ins. diam., bears S. 52¼° W., 4½ lks.
dist. with healed blaze. (Record, S. 71° W.)

A fir, 22 ins. diam., bears N. 25° W., 41 lks.
dist. with healed blaze. (Record, N. 11½° W.)

N. 88° 55' W., bet. secs. 11 and 14, marking and blazing
the true line.

Ascend over broken NE. slope, changing to SE. slope,
through heavy timber and dense undergrowth.

9.20 Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.

18.60 Spur, slopes SW.; desc. over broken SW. slope.

39.33 The ¼ sec. cor. of secs. 11 and 14, determined from the
remains of the original bearing trees:

A fir root crown, size indeterminate, bears
N. 36° E., 95 lks. dist., no marks visible.

A sawed pine stump, 50 ins. diam., bears
S. 50° E., 30 lks. dist., with axe marks
visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 32 S R 7 W

¼ S 11
S 14

1984

from which new bearing trees

A fir, 6 ins. diam., bears N. 51° E., 9 lks.
dist., mkd. ¼ S11 BT.

A fir, 6 ins. diam., bears S. 69° W., 26½ lks.
dist., mkd. ¼ S14 BT.

S. 88° 27' W., beginning new measurement.

Descend over SW. slope.

1.75 Ravine, drains S.; asc. over SE. slope.

3.60 Spur, slopes S.; desc. over SW. slope.

22.10 Ravine, drains S. 20° W.; asc. over SE. slope

27.50 Dirt road, 15 lks. wide, bears N. 20° E. and S. 75° W.,
in curve.