

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

17975

CHAINS

- 28.20 Spur, slopes S.; desc. over SW. slope.
- 33.75 Ravine, drains S.; asc. over SE. slope.
- 38.35 Spur, slopes S.; desc. over SW. slope.
- 39.00 The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 32 S R 7 W
 S 10 | S 11
 S 15 | S 14

1967

from which the remains of the original bearing trees

A pine, 38 ins. diam., bears N. 70° E., 152 lks. dist., with fragmentary scribe marks visible on opened blaze.

A pine root crown, size indeterminate, bears S. 45° E., 223 lks. dist., no marks visible. (Record 228 lks.)

A live oak root crown, size indeterminate, bears N. 65° W., 94 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Powell

A madrone, 9 ins. diam., bears N. 56° E., 45 lks. dist., with scribe marks R7W S11 CS BT visible on partially healed double blaze.

A fir, 11 ins. diam., bears S. 42° E., 43 lks. dist., with healed blaze.

A madrone snag, 6 ins. diam., bears S. 49° W., 13½ lks. dist., with scribe marks T32S R7W S15 CS BT visible on open double blaze.

A madrone, 8 ins. diam., bears N. 43½° W., 21 lks. dist., with scribe marks T32S R7W S10 CS BT visible on open double blaze.

and a new bearing tree

A fir, 4 ins. diam., bears S. 54° W., 15 lks. dist., mkd. X BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, pine, alder, yew, cedar, oak, maple, and chinquapin; undergrowth, poison oak, hazel, salal, manzanita, rhododendron, ceanothus, arrowwood, Oregon grape, vine maple, ferns, blackberry, and young timber.