

County Surveyor's Record, Douglas County, Oregon

17977

T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 11, Township 29 South, Range 7 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

A portion of the subdivisional lines was surveyed by Nathaniel Ford, U.S. Deputy Surveyor, in 1854.

A portion of the subdivisional lines was dependently resurveyed by Hans W. Thielsen, Cadastral Surveyor, in 1957.

A portion of the subdivisional lines dependently (correctively) resurveyed by Hans W. Thielesen, Cadastral Surveyor, in 1959.

A portion of the north boundary and subdivisional lines was dependently resurveyed and sections 3, 23, and 33 were subdivided by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, in 1981.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instruction, 1973, and the Special Instructions dated May 1, 1984, for Group No. 1208, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

The geographic position of the 1/4 section corner of sections 2 and 11, as determined from a tie to United States, Coast and Geodetic Survey triangulation station "Two Oaks", is as follows:

Latitude 43° 04' 16.84" N. Longitude 123° 29' 42.63" W.

The mean magnetic declination is 18° 00' E.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford, in 1854, and the (corrective) resurvey by Hans W. Thielsen, in 1959)

Beginning at the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.